

UltraClean™ UCW3700

**Polystyrenic Gel Mixed Bed
Resin Hydrogen form Hydroxide
Form**

Ultrapure Water Grade

PRINCIPAL APPLICATIONS

- Ultrapure Water

TYPICAL PACKAGING

- 1 CF Box
- 50 L Drum (plastic)
- 5 CF Drum (Fiber)

SYSTEMS

- Mixed bed demineralizer

REGULATORY APPROVALS

- IFANCA Halal Certified

TYPICAL PHYSICAL & CHEMICAL CHARACTERISTICS:

Appearance	Spherical Beads	
TOC (max.)	< 10 ppb TOC after 40 BV of rinse at 30 BV/h (*)	
Resistivity	> 18 M cm after 15 BV rinse at 30 BV/h (*)	
Shipping Weight (approx.)	685 - 725 g/L (42.8 - 45.3 lb/ft ³)	
Temperature Limit	60 °C (140.0 °F)	
Component Name	UltraClean Grade Gel Cation	UltraClean Grade Gel Type I Anion
Polymer Structure	Gel polystyrene crosslinked with divinylbenzene	Gel polystyrene crosslinked with divinylbenzene
Functional Group	Sulfonic Acid	Type I Quaternary Ammonium
Ionic Form	H	OH
Cation / Anion Chemical Equivalent Ratio	1	1
Total Capacity (min.)	1.9 eq/L (H form)	1 eq/L (OH form)
Mean Diameter	610 ± 40 µm	570 ± 50 µm
Conversion (min.)	99.9 % (H form)	95 % (OH form)
Moisture Retention	49 - 54 % (OH form)	60 - 70 %
Uniformity Coefficient	1.2	1.2
Footnote	* Influent rinse water quality : > 17.5 M .cm; < 2 ppb TOC	



Americas
T +1 610 668 9090
F +1 610 668 8139
americas@purolite.com

Europe
T +44 1443 229334
F +44 1443 227073
europe@purolite.com

Asia Pacific
T +86 571 876
31382
F +86 571 876
31385
asiapacific@purolite.com