

SALES SPECIFICATION SHEET

AMERISORB CAT 12X40

Granular Activated Carbon

Test	Specification		Calgon Carbon Test Method
	Min	Max	
IODINE NUMBER, mg/g	825	-	TM-4,ASTM D4607
MOISTURE (AS PACKAGED), wt%	-	3	TM-1,ASTM D2867
DENSITY (APPARENT), g/cc	T&R	-	TM-7,ASTM D2854
12 US MESH [1.70 mm], wt%	-	5	TM-8,ASTM D2862
< 40 US MESH [0.425 mm] (PAN), wt%	-	5	TM-8,ASTM D2862

Typical Properties:

This product complies with ANSI/AWWA B604 (Latest Edition) – Granular Activated Carbon.

This product complies with the requirements for activated carbon as defined by the Food Chemicals Codex (FCC) (Latest Edition) published by the U.S. Pharmacopeia.

Only products bearing the NSF Mark are Certified to NSF/ANSI/CAN 61 - Drinking Water System Components - Health Effects standard. Certified Products will bear the NSF Mark on packing or documentation shipped with the product.

Calgon Carbon Corporation's activated carbon products are continuously being improved and changes may have taken place since this publication went to press. -06/11/2025



+1 800 422 7266 calgoncarbon.com

CalgonCarbon
A Kuraray Company